

freshlick

The following Safety Datasheet is provided by **Prestonett**

freshlick cannot be held liable for the information contained within this document.

For purchasing information visit:
[Prestonett Ready Mixed Wood Repair Filler](#)

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: "SORTED" ALL METALS PRIMER

Product code: WP45

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Company name: Bradite Paints
Ogwen Valley Works
Bethesda
Gwynedd
LL57 4YP
United Kingdom

Tel: +44 (0)1248 600315

Fax: +44 (0)1248 602782

Email: sales@bradite.com

1.4. Emergency telephone number

Emergency tel: +44 (0)1248 600315
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411

Most important adverse effects: Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS09: Environmental



Precautionary statements: P273: Avoid release to the environment.

P391: Collect spillage.

P501: Dispose of contents/container to hazardous or special waste collection point.

SAFETY DATA SHEET
"SORTED" ALL METALS PRIMER

Page: 2

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TRIZINC BIS(ORTHOPHOSPHATE) - REACH registered number(s): 01-2119485044-40-0001

EINECS	CAS	PBT / WEL	CLP Classification	Percent
231-944-3	7779-90-0	-	Aquatic Chronic 1: H410; Aquatic Acute 1: H400	1-10%

1-METHOXY-2-PROPANOL

203-539-1	107-98-2	-	Flam. Liq. 3: H226; STOT SE 3: H336	1-10%
-----------	----------	---	-------------------------------------	-------

ZINC OXIDE - REACH registered number(s): 01-2119463881-32

-	1314-13-2	-	Aquatic Chronic 1: H410; Aquatic Acute 1: H400	<1%
---	-----------	---	------------------------------------------------	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Not applicable.

[cont...]

SAFETY DATA SHEET
"SORTED" ALL METALS PRIMER

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Wash the spillage site with large amounts of water.
Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

Storage quantity limits: N/A

7.3. Specific end use(s)

Specific end use(s): PC9a: Coatings and paints, thinners, paint removers.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

1-METHOXY-2-PROPANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA		15 min. STEL	
	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	375 mg/m ³	560 mg/m ³	-	-

SAFETY DATA SHEET
"SORTED" ALL METALS PRIMER

Page: 4

ZINC OXIDE

UK	5 mg/m ³	10 mg/m ³	-	-
----	---------------------	----------------------	---	---

DNEL/PNEC Values

Hazardous ingredients:

TRIZINC BIS(ORTHOPHOSPHATE)

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	5 mg/m ³	Workers	Systemic
DNEL	Dermal	83 mg/kg bw/day	Workers	Systemic
DNEL	Dermal	83 mg/kg bw/day	Consumers	Systemic
DNEL	Inhalation	2.5 mg/m ³	Consumers	Systemic
DNEL	Oral (repeated dose)	0.83 mg/kg bw/day	Consumers	-
PNEC	Fresh water	20.6 ugZn/L	-	-
PNEC	Marine water	6.1 ugZn/L	-	-
PNEC	Fresh water sediments	117.8 mgZn/kg sedime	-	-
PNEC	Marine sediments	56.5 mg Zn/kg sedime	-	-
PNEC	Soil (agricultural)	35.6 mgZn/kg soil dw	-	-
PNEC	Microorganisms in sewage treatment	100 ugZn/L	-	-

ZINC OXIDE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	5 mg/m ³	Workers	Systemic
DNEL	Dermal	83 mg/kg bw/day	Workers	Systemic
DNEL	Dermal	83 mg/kg bw/day	Consumers	Systemic
DNEL	Inhalation	0.83 mg/kg bw/day	Consumers	Systemic
PNEC	Fresh water	20.6 ugZn/L	-	-
PNEC	Marine water	6.1 ugZn/L	-	-
PNEC	Fresh water sediments	117.8 mgZn/kg sedime	-	-
PNEC	Marine sediments	56.6 mgZn/kg sedimen	-	-
PNEC	Soil (agricultural)	35.6 mgZn/kg soil dw	-	-
PNEC	Microorganisms in sewage treatment	100 ugZn/L	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

[cont...]

SAFETY DATA SHEET
"SORTED" ALL METALS PRIMER

Page: 5

Respiratory protection: Respiratory protection not required.
Hand protection: Protective gloves.
Eye protection: Tightly fitting safety goggles.
Skin protection: Protective clothing.
Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Grey
Odour: Barely perceptible odour
Evaporation rate: Slow
Oxidising: Non-oxidising (by EC criteria)
Solubility in water: Miscible in all proportions
Viscosity: Non-viscous
Boiling point/range°C: >100
Flammability limits %: lower: Not applicable.
Flash point°C: >93
Autoflammability°C: Not applicable.
Relative density: 1.38
VOC g/l: 41
Melting point/range°C: No data available.
upper: Not applicable.
Part.coeff. n-octanol/water: No data available.
Vapour pressure: No data available.
pH: 8.5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

[cont...]

SAFETY DATA SHEET
"SORTED" ALL METALS PRIMER

Page: 6

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

TRIZINC BIS(ORTHOPHOSPHATE)

ORAL	RAT	LD50	> 5000	mg/kg
------	-----	------	--------	-------

1-METHOXY-2-PROPANOL

IVN	RAT	LD50	4200	mg/kg
ORL	MUS	LD50	11700	mg/kg
ORL	RAT	LDLO	3739	mg/kg

ZINC OXIDE

DUST/MIST	RAT	4H LC50	> 5.7	mg/l
ORAL	RAT	LD50	> 15000	mg/kg
ORL	MUS	LD50	7950	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

TRIZINC BIS(ORTHOPHOSPHATE)

ALGAE	72H ErC50	0.14 - 0.32	mg/l
Ceriodaphnia dubia	48H EC50	0.89 - 0.96	mg/l
Daphnia magna	48H EC50	> 2.34	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	0.14 - 5.59	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

[cont...]

SAFETY DATA SHEET
"SORTED" ALL METALS PRIMER

Page: 7

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Not applicable.

Waste code number: 08 01 12

Disposal of packaging: Retain for recovery.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

[cont...]

SAFETY DATA SHEET
"SORTED" ALL METALS PRIMER

Page: 8

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.