

# freshlick

The following Product Datasheet is provided by **Zinsser**

freshlick cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Zinsser Wallpaper Cover-Up](#)

# Technical Data Sheet

## Wallpaper Cover-Up

---

**Zinsser Wallpaper Cover-Up** the smart way to paint over wallpaper. All-in-one primer, sealer & stain block - a high hiding primer that obliterates wallpaper print with a smooth matt off-white finish. Use under any coloured emulsion.

### PERFORMANCE CHARACTERISTICS:

- Obliterates wallpaper print
- Prevents blistering of wallpaper
- Blocks water soluble stains

**SURFACE PREPARATION:** For best results, ensure surface is smooth, clean, dry and free from any surface contaminants. Wallpaper must be well adhered to the surface.

**APPLICATION:** Stir thoroughly before use. Apply when temperature is between 10-30°C to ensure proper drying. Best results are achieved by roller application – Use a short pile (up to 5mm) mohair or microfibre roller. Apply evenly and avoid overspreading. If applying by brush, load generously and avoid overspreading. For very dark wallpapers or those which have a contrasting print, obliteration can be improved by using a ‘wet on wet’ rolling technique. 15-30 minutes after application, roll over the applied surface again using a lightly loaded roller.

**DRY TIME:** Touch dry within 2-4 hours. Allow a minimum of 4 hours before over painting with a good quality wall paint.

**COVERAGE:** 5-8m<sup>2</sup> per litre. Uneven surfaces or a thicker coat will reduce coverage.

**CLEANUP:** Remove as much product as possible from equipment before cleaning with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

**LIMITATIONS:** For best results, limit brush application to ‘cutting in’. Avoid using a heavy pile roller – short pile gives a smoother, more even finish. Ensure application area is well ventilated to facilitate drying.

**Drying:** Touch dry 2-4 hours, hard dry 4 hours.

**Recoat:** 4 hour at 20°C.

**Note:** Drying and recoat times will be extended at a lower temperature.

**Spread Rate:** 5-8m<sup>2</sup> per litre per coat.

**Colour Range:** Off-white

**Finish:** Matt

**Weight Solids:** 80.0+/-2%

**Volume Solids:** 56.6+/-2%

**Typical film thickness per coat:** 125-200 microns @ 5-8 m<sup>2</sup> / litre.

**VOC:** (Cat. IIA/g limit 350g/l) <335g/l

**Storage:** 5 – 30°C

**Shelf life:** 3 years in unopened containers

**Method of Application:** Brush, Pad or Roller.

**Thinner:** Not normally required.

**Cleaner:** White spirits for cleaning equipment.